


CAFL4U



connectwell
THE RIGHT CONNECTION

4 sq.mm Fuse Terminal Blocks

These Terminal Blocks are used in electrical and control systems which require fuse protection. This Terminal Blocks accepts industry standard 6.3 X 32 mm glass cartridge fuses.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	6.3 A
Tightening Torque	0.5 Nm
Housing Material	Polymide
Product Function	Single Level Fuse
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 32/DIN 35/DIN 35-15 Rail
Screw Size	M3
Operated by	Screwdriver
Rated Surge Voltage	5 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	4 mm ²
Conductor Cross Section AWG/Kcmil min	22 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	4 mm ²
2 Conductors with same Cross Section Stranded min	0.2 mm ²
2 Conductor with same Cross Section Stranded max	2.5 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	6 mm ²
2 Conductors with same Cross Section Stranded with TWIN Ferrule/Lug min	0.2 mm ²
2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max	2.5 mm ²
Stripping Length	9.5 mm
Internal Cylindrical Gauge	A4

DIMENSIONS

Height with DIN 32 rail	60.3 mm
Height with DIN 35 x 15 mm rail	63 mm
Height with DIN 35 x 7.5 mm rail	55.3 mm
Length	72 mm
Width (Thickness)	9 mm

FUSE SPECIFICATIONS

Fuse Type	Cartridge glass fuse
-----------	----------------------

FUSE SPECIFICATIONS

Fuse Size	6.3x32 mm
Fuse Current Rating	6.3 A

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CAFL4U	4 sqmm Fuse Terminal Block in Grey Colour.	25
CAFL4UBU	4 sqmm Fuse Terminal Block in Blue Colour.	25
CAFL4UBK	4 sqmm Fuse Terminal Block in Black Colour.	25
CAFL4UW/F	4 sq.mm Fuse Terminal Block in Grey Colour.	25

ACCESSORIES

IMAGES

CAT. NO.

DESCRIPTION

STD. PACK

	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50

	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50


	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50

	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
--	-------	--	----

	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
--	-------	--	----

	EPCAFL4U	End Plate in Grey colour	25
--	----------	--------------------------	----

CAFL4U


connectwell
 THE RIGHT CONNECTION

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA716/2	External Comb Type Shorting Link available in 2 Pole	50
	CA716/3	External Comb Type Shorting Link available in 3 Pole	50
	CA716/4	External Comb Type Shorting Link available in 4 Pole	50
	CA716/10	External Comb Type Shorting Link available in 10 Pole	20
	CA716/5-3A	External Comb Type Shorting Link 3 pole alternate suitable for CB16/3H	50
	CA509/K9	Blank Marking Tag	100
	CA509/K9F	Blank Marking Tag	10
	SCS0.6/3.5	Electricians Screwdriver for slotted screws	10

APPROVALS



RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	UL 1059
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	22 AWG	22 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	10 AWG	10 AWG	4 mm ²
Rated Voltage	600 V	600 V	1000 V
Rated Current	16 A	16 A	6.3 A
Tightening Torque	7 lb-in	7 lb-in	0.5 Nm

Website : rujutaent.com
 Email : rujutaent@gmail.com
 9082463426 , 8169580098
 9820825440 , 9769789105

2 of 2