

CENC35



35 sq.mm Neutral / Earth Clamps

The CENC series clamps are a flexible solution for terminating neutral and grounding wires on bus bar.

TECHNICAL DATA

| | |
|------------------------|-------------------------|
| Tightening Torque | 2.5 Nm |
| Housing Material | Polymide |
| Product Function | Neutral/Earthing Clamps |
| Wire Entry Orientation | Side Entry |
| Mounting Possibility | Panel/Surface |
| Operated by | Screwdriver |
| Rated Surge Voltage | 8 KV |
| Pollution Degree | 3 |

CONNECTION DATA

| | |
|---|--------------------|
| Conductor Cross Section Stranded min. | 10 mm ² |
| Conductor Cross Section Stranded max. | 35 mm ² |
| Conductor Cross Section AWG/Kcmil min | 8 AWG |
| Conductor Cross Section AWG/Kcmil max | 2 AWG |
| Conductor Cross Section Stranded with Ferrule/Lug min | 10 mm ² |
| Conductor Cross Section Stranded with Ferrule/Lug max | 35 mm ² |
| 2 Conductors with same Cross Section Stranded min | 10 mm ² |
| 2 Conductor with same Cross Section Stranded max | 25 mm ² |
| Stripping Length | 16 mm |

DIMENSIONS

| | |
|-------------------|---------|
| Length | 27.3 mm |
| Width (Thickness) | 14.5 mm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------|---|-----------|
| CENC35 | 35 sq.mm Neutral/Earth clamps Terminal Block in Green colour | 50 |
| CENC35BU | 35 sq.mm Neutral/Earth clamps Terminal Block in Blue colour | 50 |
| CENC35BK | 35 sq.mm Neutral / Earth Clamps Terminal Block in Black colour. | 50 |
| CENC35G | 35 sq.mm Neutral / Earth Clamps Terminal Block in Grey colour. | 50 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|----------|--|-----------|
| | CA202 | End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails | 25 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|----------|---|-----------|
| | CA509/K6 | Blank Marking Tag | 100 |
| | NES | Plastic support with fixing screw for fixing 10 / 6 mm Bus Bar suitable for mounting CENC4 / CENC16 / CENC35 Earth / Neutral Clamps | 50 |
| | SCS1/5.5 | Electricians Screwdriver for slotted screws | 10 |
| | NEB6 | 6mm Bus Bar for mounting CENC4 / CENC16 / CENC35 Earth / Neutral Clamps | 1 |
| | NEB10 | 10mm Bus Bar for mounting CENC4 / CENC16 / CENC35 Earth / Neutral Clamps | 10 |

APPROVALS



CENC35



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

| STANDARDS | UL 1059 | CSA C.22.2 No:158 | DIN EN60947-7-1 |
|---------------------------------------|----------------|--------------------------|------------------------|
| Approvals | UL | CSA | VDE |
| Conductor Cross Section Stranded min. | 8 AWG | 8 AWG | 10 mm ² |
| Conductor Cross Section Stranded max. | 2 AWG | 2 AWG | 35 mm ² |
| Tightening Torque | 25 lb-in | 25 lb-in | 2.5 Nm |

| STANDARDS | IEC/EN60947-7-1 |
|---------------------------------------|------------------------|
| Approvals | CE |
| Conductor Cross Section Stranded min. | 10 mm ² |
| Conductor Cross Section Stranded max. | 35 mm ² |
| Tightening Torque | 2.5 Nm |

Website : rujutaent.com
Email : rujutaent@gmail.com
9082463426 , 8169580098
9820825440 , 9769789105