


CM4S



connectwell
THE RIGHT CONNECTION

4 sq. mm spring clamp Panel Mount Terminal Blocks.

A perfect solution for extremely compact wiring applications, these terminal block are modular and can be stacked to form multi-pole terminal block assemblies. CM series terminal Block have a side sere entry configuration.

TECHNICAL DATA

Rated Voltage	630 V
Rated Current	32 A
Housing Material	Polymide
Product Function	Feed Through
Wire Entry Orientation	Side
Mounting Possibility	Free Floating / Surface / Panel
Operated by	Screw Driver
Rated Surge Voltage	6 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	4 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	1.5 mm ²
2 Conductors with same Cross Section Stranded min	0.2 mm ²
2 Conductor with same Cross Section Stranded max	1.5 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	4 mm ²
Stripping Length	10 mm

DIMENSIONS

Height	23 mm
Length	33.7 mm
Width (Thickness)	7 mm




ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CM4S	4 sqmm Panel Mount Spring ClampTerminal Block in Grey colour.	100
CM4SBK	4 sqmm Panel Mount Spring ClampTerminal Block in Black colour.	100
CM4SBU	4 sqmm Panel Mount Spring ClampTerminal Block in Blue colour.	100
CM4SGN	4 sqmm Panel Mount Spring ClampTerminal Block in Green colour.	100
CM4SR	4 sqmm Panel Mount Spring ClampTerminal Block in Red colour.	100


ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CM4SY	4 sqmm Panel Mount Spring ClampTerminal Block in Yellow colour.	100
CM4SYG	4 sqmm Panel Mount Spring ClampTerminal Block in Yellow-Green colour.	100
CM4SO	4 sqmm Panel Mount Spring ClampTerminal Block in Orange colour.	100

ACCESSORIES


IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	SCS0.5/3	Electricians Screwdriver for slotted screws	10
	CA509/K6	Blank Marking Tag	100
	EPCM4S	End Plate in Grey Colour	50

APPROVALS



Website : rujutaent.com
 Email : rujutaent@gmail.com
 908463426, 8169580098
 9820825440, 9769789105

CM4S



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	IEC/EN60947-7-1
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	10 AWG	10 AWG	4 mm ²
Rated Voltage	300 V	300 V	630 V
Rated Current	26 A	26 A	32 A

Website : rujutaent.com
Email : rujutaent@gmail.com
9082463426 , 8169580098
9820825440 , 9769789105