


CXDL2.5(E)L D1



connectwell
THE RIGHT CONNECTION

2.5 sq.mm Double Level Terminal Blocks with LED indication -LD1 Configuration

Double Level Terminal Block are available with DC voltage indicator with LED

THIS PRODUCT IS NOT FOR SALE IN GERMANY

TECHNICAL DATA

| | |
|------------------------|--|
| Rated Voltage | 1000 V |
| Rated Current | 1 A |
| Housing Material | Polymide |
| Product Function | With Electronic Components: Diode/Resistor |
| Wire Entry Orientation | Top Entry |
| Mounting Possibility | DIN 35/DIN 35-15 Rail |
| Operated by | Screwdriver |
| Rated Surge Voltage | 8 KV |
| Pollution Degree | 3 |

CONNECTION DATA

| | |
|---------------------------------------|---------------------|
| Conductor Cross Section Stranded min. | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 2.5 mm ² |
| Conductor Cross Section AWG/Kcmil min | 24 AWG |
| Conductor Cross Section AWG/Kcmil max | 12 AWG |
| Stripping Length | 10 mm |

DIMENSIONS

| | |
|----------------------------------|---------|
| Height | mm |
| Height with DIN 15 x 5 mm rail | mm |
| Height with DIN 32 rail | mm |
| Height with DIN 35 x 15 mm rail | 57 mm |
| Height with DIN 35 x 7.5 mm rail | 49.5 mm |
| Length | 72.7 mm |
| Width (Thickness) | 5 mm |

DIODE SPECIFICATIONS

| | |
|-----------------------|---------|
| Diode Type | 1N4007 |
| Diode Forward Current | 1 A |
| Diode Maximum Voltage | 300 VAC |
| Diode Type | 1N4007 |
| Diode Forward Current | 1 A |
| Diode Maximum Voltage | 300 VAC |
| Diode Type | 1N4007 |
| Diode Forward Current | 1 A |
| Diode Maximum Voltage | 300 VAC |
| Diode Type | 1N4007 |
| Diode Forward Current | 1 A |

DIODE SPECIFICATIONS

| | |
|-----------------------|---------|
| Diode Maximum Voltage | 300 VAC |
|-----------------------|---------|


ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|---------------|---|-----------|
| CXDL2.5(E)LD1 | 2.5 sq.mm Terminal Block with LED Indication for 6-60 V | 100 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|---------------|--|-----------|
| | CA701-1M | Din 35 Rail unslotted 1 meter | 50 |
| | CA701-2M | Din 35 Rail unslotted 2 meter | 50 |
| | CA701-2M-S | Din 35 Rail slotted 2 meter | 50 |
| | CA701-1M-S | Din 35 Rail slotted 1 meter | 50 |
| | CA701-15-1M | Din 35 Rail 15 deep unslotted 1 meter | 50 |
| | CA701-15-1M-S | Din 35 Rail 15 deep slotted 1 meter | 50 |
| | CA701-15-2M | Din 35 Rail 15 deep unslotted 2 meter | 50 |
| | CA701-15-2M-S | Din 35 Rail 15 deep slotted 2 meter | 50 |
| | CA103 | EndClamp in Polyamide suitable for Din 35/Din 35-15 rails | 50 |
| | CA702 | End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails | 50 |
| | CA802 | End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails | 50 |
| | EPCXDL2.5 | End Plate in Grey Colour | 50 |
| | JX2.5/2 | Shorting Link for 2.5 sq mm series | 100 |
| | JX2.5/3 | Shorting Link for 2.5 sq mm series | 50 |
| | JX2.5/4 | Shorting Link for 2.5 sq mm series | 50 |
| | JX2.5/5 | Shorting Link for 2.5 sq mm series | 50 |
| | JX2.5/6 | Shorting Link for 2.5 sq mm series | 50 |
| | JX2.5/7 | Shorting Link for 2.5 sq mm series | 10 |
| | JX2.5/8 | Shorting Link for 2.5 sq mm series | 10 |
| | JX2.5/10 | Shorting Link for 2.5 sq mm series | 10 |
| | CA509/K5 | Blank Marking Tag | 100 |

CXDL2.5(E)L
D1



connectwell
THE RIGHT CONNECTION

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|----------|---|-----------|
| | SCS0.5/3 | Electricians Screwdriver for slotted screws | 10 |

NOTES

THIS PRODUCT IS NOT FOR SALE IN GERMANY

CIRCUIT DIAGRAM

Hello, world!

RATINGS AS PER STANDARDS

| STANDARDS | UL 1059 | CSA C.22.2 No:158 | IEC/EN60947-7-1 |
|---------------------------------------|---------|-------------------|---------------------|
| Approvals | UL | CSA | CE |
| Conductor Cross Section Stranded min. | 24 AWG | 24 AWG | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 12 AWG | 12 AWG | 2.5 mm ² |
| Rated Voltage | 600 V | 600 V | 1000 V |
| Rated Current | 20 A | 20 A | 1 A |

Website : rujutaent.com
Email : rujutaent@gmail.com
9082463426 , 8169580098
9820825440 , 9769789105