


CXG4



connectwell
THE RIGHT CONNECTION

4 sq.mm Spring Clamp earthing compact Terminal Blocks

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.

TECHNICAL DATA

| | |
|------------------------|-----------------------|
| Housing Material | Polymide |
| Product Function | Earthing/Grounding |
| Wire Entry Orientation | Top |
| Mounting Possibility | DIN 35/DIN 35-15 Rail |
| Operated by | Screw Driver |
| Rated Surge Voltage | 8 KV |
| Pollution Degree | 3 |

CONNECTION DATA

| | |
|---------------------------------------|---------------------|
| Conductor Cross Section Stranded min. | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 4 mm ² |
| Conductor Cross Section AWG/Kcmil min | 24 AWG |
| Conductor Cross Section AWG/Kcmil max | 10 AWG |
| Conductor Cross Section Solid min | 0.2 mm ² |
| Conductor Cross Section Solid max | 6 mm ² |
| Stripping Length | 10 mm |

DIMENSIONS

| | |
|----------------------------------|---------|
| Height with DIN 35 x 15 mm rail | 45.2 mm |
| Height with DIN 35 x 7.5 mm rail | 37.6 mm |
| Length | 54.8 mm |
| Width (Thickness) | 6 mm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------|---|-----------|
| CXG4 | 4 sq.mm Earthing Spring Clamp Terminal Block in Green-Yellow colour | 100 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|---------------|---------------------------------------|-----------|
| | CA701-1M | Din 35 Rail unslotted 1 meter | 50 |
| | CA701-2M | Din 35 Rail unslotted 2 meter | 50 |
| | CA701-2M-S | Din 35 Rail slotted 2 meter | 50 |
| | CA701-1M-S | Din 35 Rail slotted 1 meter | 50 |
| | CA701-15-1M | Din 35 Rail 15 deep unslotted 1 meter | 50 |
| | CA701-15-1M-S | Din 35 Rail 15 deep slotted 1 meter | 50 |
| | CA701-15-2M | Din 35 Rail 15 deep unslotted 2 meter | 50 |
| | CA701-15-2M-S | Din 35 Rail 15 deep slotted 2 meter | 50 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|------------|--|-----------|
| | CA103 | EndClamp in Polyamide suitable for Din 35/Din 35-15 rails | 50 |
| | CA702 | End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails | 50 |
| | CA802 | End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails | 50 |
| | EPCX4 | End Plate in Grey colour | 50 |
| | EPCX4BU | End Plate in Blue colour | 50 |
| | PPCX4 | Partition Plate in Grey colour | 50 |
| | JX4/2 | Shorting Link for 6 mm wide TB | 100 |
| | JX4/3 | Shorting Link for 6 mm wide TB | 50 |
| | JX4/4 | Shorting Link for 6 mm wide TB | 50 |
| | JX4/8 | Shorting Link for 6 mm wide TB | 10 |
| | JX4/10 | Shorting Link for 6 mm wide TB | 10 |
| | CA509/K6 | Blank Marking Tag | 100 |
| | SCS0.6/3.5 | Electricians Screwdriver for slotted screws | 10 |


APPROVALS



NOTES

THIS PRODUCT IS NOT FOR SALE IN GERMANY

CXG4



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

| STANDARDS | UL 1059 | CSA C.22.2 No:158 | IEC/EN60947-7-1 |
|---------------------------------------|---------|-------------------|---------------------|
| Approvals | UL | CSA | CE |
| Conductor Cross Section Stranded min. | 24 AWG | 24 AWG | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 10 AWG | 10 AWG | 4 mm ² |

Website : rujutaent.com
Email : rujutaent@gmail.com
9082463426 , 8169580098
9820825440 , 9769789105