

PSS240/48/5



connectwell
THE RIGHT CONNECTION

5A,240W Single Phase Din Rail Mountable Switching Power Supplies

- Full Range Input selection from 90 to 264 VAC Auto select
- Typical efficiency of 90%
- Compact design with a width of only 83.5mm
- Parallel function available (Switch)
- Two years product warranty

GENERAL SPECIFICATION

Switching Frequency (typ.)	40 KHz
Min. Isolation Voltage -AC (Input-FG)	1500 VAC
Min. Isolation Voltage -AC (Input-Output)	3000 VAC
Min. Isolation Voltage -DC (Input-FG)	2121 VDC
Min. Isolation Voltage -DC (Input-Output)	4242 VAC
Isolation Resistance (Input-Output @500VDC)	100 MΩ
Ambient Temperature Range (Operational at Vi norm)	-40 to +71 deg.C
Derating from +61°C to +71°C (see derating curve)	2.5% / °C
Ambient Temperature Range (Storage)	-40 to +85 deg.C
Relative Humidity Range	20 to 95 %RH
Temperature Coefficient Range	+/- 0.03 % per deg. C
MTBF (Bellcore Issue 6 @40°C, GB)	437000 hr
Altitude During Operation (IEC 60068-2-13)	4850 m
Dimension	Screw terminal type L124.5 X W83.5 X D123.6 mm
Cooling	Free Air Convection
Pollution Degree	2

ORDERING INFORMATION

Cat. No.	PSS240/48/5
Output Voltage	48 VDC
Output Current	5 A
Output Wattage	240 W
Efficiency (min.)	88%
Efficiency (typ.)	90%
Input Voltage Range	115~230 VAC
Standard Packing Qnty	1

PHYSICAL SPECIFICATIONS

Dimensions (H x W x D)	124.5 X 83.5 X 123.6 mm
Weight	1380g
Case Material	Metal
Packing	1.5kg ; 16 pcs / 25 kg / 2.01 CUFT

APPROVALS



ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	SCPH1	Phillips Screwdriver for Phillips Recess screws	10

STANDARD USED FOR TESTING

UL/cUL	UL 508 Listed UL 60950-1, UL 1310 Class 2 Power (24V/E Models only) Recognized ISA 12.12.01 (Class I, Division 2, Groups A, B, C, and D)
TUV	EN 60950-1, CB scheme , EN 61558-1, EN 61558-2-17 (meet EN 60204)
CE	EN 61000-6-3, EN 55022 Class B, EN 61000-3-2, EN 61000-3-3 E N 61000-6-2, EN 55024, EN 61000-4-2 Level 4, EN 61000-4-3 Level 3 EN 61000-4-4 Level 4, EN 61000-4-5 L-N Level 3, L / N-FG Level 4 EN 61000-4-6 Level 3, EN 61000-4-8
CCC	GB4943, GB9254, GB17625.1
Vibration Resistance	meet IEC 60068-2-6 (Mounting by rail : 10-500 Hz, 2G, along X, Y, Z each Axis, 60 min for each Axis)
Shock Resistance	meet IEC 60068-2-27 (15G, 11ms, 3 Axis, 6 Faces, 3 times for each Face)

PSS240/48/5



connectwell
THE RIGHT CONNECTION

INPUT SPECIFICATIONS

Input Phase	Single
Rated Input Voltage	115 /230 VAC (auto select)
DC Input Voltage Range	210 to 375
Input Voltage Range (115VAC Selected)	90 to 132 VAC
Input Voltage Range (230VAC Selected)	180 to 264 VAC
Line Frequency-Max.	63 Hz
Line Frequency-Min.	47 Hz
Max. Inrush Current (Vi: 115 VAC)	30 A
Max. Inrush Current (Vi: 230 VAC)	60 A
Rated Input Current -Typ. (Vi : 115 VAC)	4.0 A
Rated Input Current -Typ. (Vi : 230 VAC)	1.55 A
Rated Input Current -Max. (Vi : 115 VAC)	5.4 A
Rated Input Current -Max. (Vi : 230 VAC)	2.2 A
Power Dissipation (Vi: 230 VAC, Io norm)	32 W
Leakage Current (Input-Output)	0.25 mA
P.F.C.	0.7 typ.

OUTPUT SPECIFICATIONS

Output Voltage	48 VDC
Output Current	5 A
Output Voltage Accuracy (Adjusted before shipment)	0 to +1 %
Minimum Load	0 %
Line Regulation	+/- 0.5 %
Load Regulation: Single Mode	+/- 1 %
Load Regulation: Parallel Mode	+/- 5 %
Output Voltage Trim Range	47 to 56 VDC
Rated Continuous Loading	5A @48Vdc / 4.2A @56Vdc
Hold Up Time (Vi: 115VAC)	25 msec
Hold Up Time (Vi: 230VAC)	30 msec
Turn On Time	1000 ms
Turn On Time With 7000 μ F	1500 msec
Rise Time	150 ms
Rise Time With 7000 μ F	500 ms
Fall Time	150 msec
Transient Recovery Time	2 ms
Ripple and Noise (BW = 20MHz)	100 mV
Power Back Immunity	63 V
Capacitor Load	7000 μ F
DC ON Indicator Threshold at start up (Green LED)	37.0 to 43.0 VDC
DC LOW Indicator Threshold after start up (Red LED)	37.0 to 43.0 VDC
Parallel Operation	3 unit
Efficiency	90%

PIN CONFIGURATION

PIN NO	POSITION	DESIGNATION	DESCRIPTION
1	OUT	RDY	A normal open relaycontact for DC ON level control
2	OUT		(never connect except 24V/E model)
3,4	OUT	V+	Positive output terminal
5,6	OUT	V-	Negative output terminal
7	IN	Ground	Ground this terminal to minimize high frequency emmissions
8	IN	L	Input terminals(phase conductor, no polarity at DC input))
9	IN	N	Input terminals (neutral conductor, no polarity at DC input)
	OTHER	DC ON	Operation indicator LED
	OTHER	DC LO	DC LOW voltage indicator LED
	OTHER	Vout ADJ.	Trimmer-potentiometer for Vout adjustment
	OTHER	S/P	Single / Parallel select switch