

# STH4DT



**connectwell**  
THE RIGHT CONNECTION

## Stud Type Terminal Block

These Terminal Blocks are preferred for applications where the connections are subjected to severe vibrations. The wire is crimped to ring /fork type Lug (Ferrule) and is screwed on to flat current bar on the Terminal Block. The fastening nut always remains captive in the hinged plastic carrier. The Hinged Carrier should be lifted to insert the lugs and then snapped back into position. The nut can then be fastened to complete the connection. By the virtue of the hinged design the Terminal Blocks apart from shrouding the live parts, providing IP20 protection, saves considerable time in wiring. STH4DT Disconnect & Test Terminal Block is used for measuring, control and regulatory circuits. They provide a clear functional advantage for devices having utility instruments and associated transformers. Seperate testing points facilitate insertion of test probes. Disconnection is achieved by means of slide link operated with a screwdriver.

### TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	41 A
Tightening Torque	1.2 Nm
Housing Material	Polymide
Product Function	Feed Through
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 32/DIN 35/DIN 35-15 Rail
Stud Size	M4
Operated by	Screwdriver
Rated Surge Voltage	8 KV
Pollution Degree	3

### CONNECTION DATA

Conductor Cross Section Stranded min.	1.5 mm <sup>2</sup>
Conductor Cross Section Stranded max.	6 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	22 AWG
Conductor Cross Section AWG/Kcmil max	8 AWG
2 Conductors with same Cross Section Stranded min	1.5 mm <sup>2</sup>
2 Conductor with same Cross Section Stranded max	6 mm <sup>2</sup>
Conductor Cross Section Solid min	1.5 mm <sup>2</sup>
Conductor Cross Section Solid max	6 mm <sup>2</sup>

### DIMENSIONS

Height with DIN 32 rail	56.4 mm
Height with DIN 35 x 15 mm rail	59 mm
Height with DIN 35 x 7.5 mm rail	52.2 mm
Length	86 mm
Width (Thickness)	11 mm

### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
STH4DT	6 Sq.mm Hinge Type Disconnect and Test Terminal Block in Grey Colour	50
STH4DTBU	6 Sq.mm Hinge Type Disconnect and Test Terminal Block in Blue Colour	50

### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
STH4DTR	6 Sq.mm Hinge Type Disconnect and Test Terminal Block in Red Colour	50
STH4DTY	6 Sq.mm Hinge Type Disconnect and Test Terminal Block in Yellow Colour	50
STH4DTBK	6 Sq.mm Hinge Type Disconnect and Test Terminal Block in Black Colour	50

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50

	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50

	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50


	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
--	-------	--	----

	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
--	-------	--	----

	EPSTH4DT	End Plate in Grey colour suitable for STH4DT / STH4DTSH Terminal Block	50
--	----------	--	----

	CA514/13-2	Insulated Removable Shorting Link available in 2 Pole	100
	CA514/13-3	Insulated Removable Shorting Link available in 3 Pole	50
	CA514/13-4	Insulated Removable Shorting Link available in 4 Pole	50

STH4DT



**connectwell**  
THE RIGHT CONNECTION

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	QJ11/2	2 Pole shorting Plug for STH4DT Terminal Block	25
	QJ11/4	4 Pole shorting Plug for STH4DT Terminal Block	25
	CA514/14-2	Insulated Ring Type Shorting Link for 2 way Shorting	100
	CA514/14-3	Insulated Ring Type Shorting Link for 3 way Shorting	50
	CA514/14-4	Insulated Ring Type Shorting Link for 4 way Shorting	50
	CA514/14-3A	Insulated 3 way Alternate Type Shorting Link	10
	CA514/14-4A	Insulated 4 way Alternate Type Shorting Link	10
	CA512/13-2	Removable Shorting link available in 2 Pole	100
	CA512/13-3	Removable Shorting link available in 3 Pole	50
	CA512/13-4	Removable Shorting link available in 4 Pole	50
	CA512/14-2	Ring Type Shorting Link for 2 way Shorting	100
	CA512/14-3	Ring Type Shorting Link for 3 way Shorting	50
	CA512/14-4	Ring Type Shorting Link for 4 way Shorting	50
	CA509/K10	Marking Tag Blank suitable for CTS10U / CGT10U / CGT10N / CHV10U / CTS10USC / STH4 / STH4DT / STH4DTSH / CSC10T Terminal Blocks	100
	SCS1/5.5	Electricians Screwdriver for slotted screws	10
	LCSTH4DT	Lock Out Cap for STH4DT Terminal Block	50

**APPROVALS**



**RATINGS AS PER STANDARDS**

STANDARDS	IEC/EN60947-7-1	UL 1059	CSA C.22.2 No:158
Approvals	CE	UL	CSA
Conductor Cross Section Stranded min.	1.5 mm <sup>2</sup>	22 AWG	22 AWG
Conductor Cross Section Stranded max.	6 mm <sup>2</sup>	8 AWG	8 AWG
Rated Voltage	1000 V	600 V	600 V
Rated Current	41 A	35 A	35 A
Tightening Torque	1.2 Nm	14 lb-in	14 lb-in